

PRODUCT-DETAILS

3KDE175521L9500

AI950S Temperature (TI4-Ex)



General Information

3KDE175521L9500 2

Product ID3KDE175521L9500ABB Type DesignationAl950SCatalog DescriptionAl950S Temperature (TI4-Ex)

The remote S900 I/O system can be installed in non-hazardous areas or directly in Zone 1 or Zone 2 hazardous area depending on the selected system variant. S900 I/O communicates with the control system level using PROFIBUS DP standard. The I/O system can be installed directly in the field, therefore the costs for mashalling and wiring are reduced.

The system is sturdy, error-tolerant and easy to service. Integrated disconnection mechanisms allow replacement during operation, meaning that there is no need to interrupt the primary voltage in order to exchange the power supply units.

S900 I/O type S. For installation in hazardous area Zone 1. For connecting intrinsically safe field devices installed in Zone 2 or Zone 1 or Zone 0.

Al950S Temperature Input (TI4-Ex), supporting Pt100, Pt1000, Ni100 in 2-/3-/4-technology. Thermocouples type B, E, J, K, L, N, R, S, T, U, mV. Isolated inputs channel by channel.

Long Description

- ATEX Certification for installation in Zone 1
- Redundancy (Power and Communication)
- Hot Configuration in Run
- Hot Swap functionality
- Extended Diagnostic
- Excellent configuration and diagnostics via FDT/DTM
- G3-coating for all components
- Simplified maintenance with auto-diagnostics
- Pt 100, Pt 1000, Ni 100, 0...3kOhms in 2/3/4 wire technique
- Thermocouple Type B, E, J, K, L, N, R, S, T, U, mV
- Internal or external cold junction compensation
- Short and break detection
- Electrical isolation between input / bus and input / power
- Electrical isolation channel to channel

- 4 channels

Additional Information

 Medium Description
 AI950S Temperature (TI4-Ex)

 Product Type
 I-O_Module

Ordering

Country of Origin Germany (DE)
United States (US)
Customs Tariff Number 8538909999

Dimensions

Product Net Length104 mmProduct Net Height20 mmProduct Net Width104 mmProduct Net Weight0.135 kg

Technical

4
Al
4

3KDE175521L9500

Classifications	
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
Number of Batteries	0
RoHS Status	Following EU Directive 2011/65/EU

Categories

Control System Products \rightarrow I/O Products \rightarrow S900 I/O \rightarrow S900 I/O - Modules \rightarrow Al950S Temperatures \rightarrow Al950S Temperature Control Systems \rightarrow 800xA \rightarrow I/Os \rightarrow S900 I/O \rightarrow I/O Modules Control Systems \rightarrow 800xA \rightarrow I/Os \rightarrow S900 I/O \rightarrow I/O Modules

