GE FANUC VERSAMAX EXACT-MODEL PRODUCT

IC200ALG321

IC200ALG321 is a GE Fanuc VersaMax four-channel voltage analog output module. The manufacturer table identifies 12-bit conversion and a 0-10 V output range. Match the exact module, carrier, channel scaling, field wiring, load requirements, and saved controller configuration before replacement.

PRODUCT FAMILY	PRODUCT TYPE
VersaMax Modular I/O	**4-Channel 0-10 V Analog Output Module**

Exact model configuration

CONFIGURATION FIELD	VERIFIED VALUE / CHECK
Displayed model	**IC200ALG321**
Manufacturer	**GE Fanuc**
Product family	**VersaMax Modular I/O**
Product type	**4-Channel 0-10 V Analog Output Module**
Output channels	**4**
Output signal	**0 to 10 VDC**
Resolution	**12-bit**
Module class	**VersaMax analog output**
Mounting system	**VersaMax I/O carrier on DIN rail**
Protection rating	**IP20**
Operating temperature	**0 to 60 degrees C standard range**
Typical application	**Machine and general automation voltage outputs**
Country of origin	**USA**

Application fit

- Use only where the controlled I/O configuration specifies IC200ALG321 and four 0-10 V analog outputs.
- Confirm the exact VersaMax carrier, field terminal arrangement, load compatibility, grounding, and channel scaling.
- Preserve channel assignments and output fail-state requirements before removing the installed module.

PRODUCT-SPECIFIC REFERENCE	INSTALLATION NOTE
The Emerson VersaMax selection table identifies IC200ALG321 as a four-channel, 12-bit, 0-10 V analog output module.	Install on the verified VersaMax carrier with field power controlled, restore the approved wiring and scaling, then validate each channel from commanded value to field response.

MODEL-SPECIFIC ENGINEERING REFERENCE

Before ordering IC200ALG321

Use this page as a controlled procurement checklist. It does not replace the manufacturer instruction sheet, wiring drawing, approval certificate, or site safety procedure.

Ordering limits and selected values

CONFIGURATION FIELD	VERIFIED VALUE / CHECK
Manufacturer	**GE Fanuc**
Product family	**VersaMax Modular I/O**
Product type	**4-Channel 0-10 V Analog Output Module**
Output channels	**4**
Output signal	**0 to 10 VDC**
Resolution	**12-bit**
Module class	**VersaMax analog output**
Mounting system	**VersaMax I/O carrier on DIN rail**
Protection rating	**IP20**
Operating temperature	**0 to 60 degrees C standard range**
Typical application	**Machine and general automation voltage outputs**
Country of origin	**USA**

Procurement checklist

- Photograph the complete IC200ALG321 nameplate, revision, carrier, terminals, and installed slot.
- Export the controller configuration and record all four channel assignments, ranges, scaling, and fail states.
- Verify 0-10 V load compatibility, common reference, shielding, grounding, polarity, and conductor condition.
- Inspect the carrier latch, connector, terminal hardware, and cabinet environment before installation.
- Commission all four outputs at controlled values and record commanded versus measured voltage and field response.

DIRECT SALES INQUIRY

Send the full model **IC200ALG321**, quantity, delivery country, and a clear nameplate or installed-module photo.

Sandy Lin | plcinfo@mooreplc.com | WhatsApp /Phone: +86 18020776786

Source and document status

Technical basis	Emerson VersaMax Modular I/O and Control data sheet 00813-0100-0112 (June 2020) and applicable GE Fanuc VersaMax documentation in the Emerson knowledge center.
Publisher	Moore Automation - independent industrial automation supplier.
Document status	Independent product manual; not a manufacturer-issued datasheet, conformity certificate, or calibration certificate.
Important	Verify the complete nameplate, suffix, carrier or terminal hardware, wiring, approvals, and installed-system compatibility before ordering.